

speco technologies®

Bullet² Series Weatherproof Color Intensifier Camera



Bullet Squared:
Our new line of square
bullet cameras

HT-INTB4

Features

- 520/580 lines of resolution
- 3.8-9.5mm auto iris varifocal lens
- Minimum illumination 0.002 lux
- 30 IR LEDs with adjustable IR brightness
- Dual voltage 12V DC & 24V AC operation
- SLC - Speco Light Compensation
- Full OSD operation
- All controls easily reached for adjustment
- S/N Ratio more than 50dB (weight on)
- Weatherproof operation
- Wall/ceiling mount
- True day/night operation

Specifications

CCD Type	1/3" Sony Super-HAD* CCD
Resolution	520 TV line (IR OFF) / 580 TV line (IR ON)
Total Pixels	410K
Lens	Auto Iris Varifocal Lens (3.8-9.5mm)
Minimum Illumination	0.2 Lux / F1.2 with IR OFF (40IRE, AGC Middle, DNR Low), 0.002 Lux in Intensifier mode / F1.2 with IR ON
S/N Ratio	50dB or more (AGC OFF)
White Balance	ATW / AWC / Manual (1,800°K~10,500°K)
Video Output	1.0Vp-p (Sync. Negative) Termination 75Ω
Electronic Shutter	Auto / Manual (X128, 1/60~1/100,000 sec.) Sense-up & sense-up limit selectable
OSD	Yes
SLC (Speco Light Compensation)	Low, middle, High, Off, Selectable
Privacy Zone	ON/OFF Selectable (4 Zone)
Mirror	ON/OFF Selectable
Power Supply	24 Volts AC, 12 Volts DC - Dual Voltage
Current Consumption	600mA Max.
Scanning System	2:1 Interlace
Synchronization	Internal / External (Line-Lock)
Operating Temperature	-20°F to 122°F
Dimensions	3.1" W x 3" H x 6.8" L
Weight	3.3 lbs.

Specifications subject to change

**Super-HAD is a trademark of The Sony Corporation*

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880